

Logitank Kommander - LTKO 12

A self bunded and transportable KOMMANDER tank for the safe storage and handling of diesel, petrol and oils. Ideal for refuelling vehicles, machinery, equipment and fleet.



Tank features rounded corners designed to eliminate stress points for improved quality and greater longevity. Also designed for visibility across all external surfaces of the tank.

Specifications

Description

Safe Fill, litres	10,610
Length, mm	2,991
Width, mm	2,438
Height, mm	2,896
Tare Weight, kg	4,045
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, AS1657, UL142

Self bunded double wall design

- Fluid level dipsticks for tank and interstitial space
- UL compliant emergency relief vents on the main tank and interstitial space
- Vent stack with screened rainproof outlet
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty – 5 years structural, 1 year on valves; conditions apply

Pump bay model standard with:

- Bunded pump bay with lockable weatherproof doors
- Galvanised access ladder and platform; with ladder fitted to either side of the platform (ex-factory)
- Galvanised kick plate and middle rail provided for additional safety of users

Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras.